



- Maximum operating temperature 105°C.
- Allowable temperature rise 15K max.
- A little hum is produced when applied AC voltage.

◆SPECIFICATIONS

Items	Characteristics	
Category temperature range	-40 to +105°C	
Rated voltage range	250 to 800V <sub>dc</sub>	
Capacitance tolerance	±5% (J)	
Voltage proof (Terminal - Terminal)	No degradation, at 150% of rated voltage shall be applied for 60 seconds.	
Dissipation factor (tanδ)	No more than 0.05% : Equal or less than 1μF. No more than (c×0.015+0.05)% : More than 1μF.	
Insulation resistance (Terminal - Terminal)	No less than 30000MΩ : Equal or less than 0.33μF. No less than 10000ΩF : More than 0.33μF.	
	Rated voltage (V <sub>dc</sub> )	250   315   400   630   800
	Measurement voltage (V <sub>dc</sub> )	100   100   100   500   500
Endurance	The following specifications shall be satisfied, after 1000hrs with applying rated voltage×125% at 105°C.	
	Appearance	No serious degradation
	Insulation resistance (Terminal - Terminal)	No less than 10000MΩ : Equal or less than 0.33μF. No less than 3000ΩF : More than 0.33μF.
		Dissipation factor (tanδ)
	Capacitance change	Within ±5% of initial value.
Loading under damp heat	The following specifications shall be satisfied, after 500hrs with applying rated voltage at 40°C 90~95%RH.	
	Appearance	No serious degradation.
	Insulation resistance (Terminal - Terminal)	No less than 10000MΩ : Equal or less than 0.33μF. No less than 3000ΩF : More than 0.3μF.
		Dissipation factor (tanδ)
	Capacitance change	Within ±5% of initial value.

◆STANDARD RATINGS

WV (V <sub>dc</sub> )	Cap (μF)	Dimensions (mm)					Maximum ripple current (Arms)	WV (Vac)	Part Number	Previous Part Number (Just for your reference)
		W	H	T	F	φd				
250	0.33	16.2	8.6	8.3	10.0	0.8	3.08	125	FTACB251V334JDLCZ0	TACB2E334J
	0.39		9.2	8.8			3.34		FTACB251V394JDLCZ0	TACB2E394J
	0.47		9.7	9.3			3.67		FTACB251V474JDLCZ0	TACB2E474J
	0.56		10.3	9.8			4.01		FTACB251V564JDLCZ0	TACB2E564J
	0.68		11.1	10.6			4.42		FTACB251V684JDLCZ0	TACB2E684J
	0.82		11.9	11.4			4.85		FTACB251V824JDLCZ0	TACB2E824J
	1.0	12.9	12.3	5.35	FTACB251V105JDLCZ0		TACB2E105J			
	1.2	12.9	12.3	5.03	FTACB251V125JHLGZ0		TACB2E125J			
	1.5	14.1	13.5	5.63	FTACB251V155JHLGZ0		TACB2E155J			
	1.8	15.2	14.5	6.17	FTACB251V185JHLGZ0		TACB2E185J			
	2.2	14.5	13.8	5.04	FTACB251V225JELHZ0		TACB2E225J			
	2.7	15.7	15.0	5.58	FTACB251V275JELHZ0		TACB2E275J			
	3.3	17.1	16.3	6.17	FTACB251V335JELHZ0		TACB2E335J			
	3.9	18.4	17.5	6.71	FTACB251V395JELHZ0		TACB2E395J			
	4.7	20.0	19.0	7.36	FTACB251V475JELHZ0		TACB2E475J			
	5.6	19.3	18.4	6.38	FTACB251V565JFLEZ0		TACB2E565J			
	6.8	21.0	20.0	7.03	FTACB251V685JFLEZ0		TACB2E685J			
	8.2	22.1	21.9	7.72	FTACB251V825JFLEZ0		TACB2E825J			
	10	25.2	24.0	8.52	FTACB251V106JFLEZ0		TACB2E106J			
	12	27.3	26.0	9.34	FTACB251V126JFLEZ0		TACB2E126J			
	15	24.2	23.1	6.45	FTACB251V156JTLJZ0		TACB2E156J			
	18	26.3	25.1	7.07	FTACB251V186JTLJZ0		TACB2E186J			
22	28.9	27.5	7.81	FTACB251V226JTLJZ0	TACB2E226J					
315	0.22	16.2	8.7	8.3	10.0	0.8	2.81	150	FTACB3B1V224JDLCZ0	TACB2F224J
	0.27		9.3	9.0			3.11		FTACB3B1V274JDLCZ0	TACB2F274J
	0.33		10.0	9.6			3.44		FTACB3B1V334JDLCZ0	TACB2F334J
	0.39		10.7	10.2			3.74		FTACB3B1V394JDLCZ0	TACB2F394J
	0.47		11.4	10.9			4.10		FTACB3B1V474JDLCZ0	TACB2F474J
	0.56		12.1	11.6			4.48		FTACB3B1V564JDLCZ0	TACB2F564J
	0.68	13.2	12.6	4.94	FTACB3B1V684JDLCZ0		TACB2F684J			
	0.82	13.2	12.6	4.65	FTACB3B1V824JHLGZ0		TACB2F824J			
	1.0	14.4	13.7	5.14	FTACB3B1V105JHLGZ0		TACB2F105J			

- (1)Capacitance tolerance : Standard (J:±5%), Option (K:±10%)
- (2)The maximum ripple current : +85°C max., 100kHz, sine wave
- (3)WV(Vac) : 50Hz or 60Hz, sine wave

### ◆STANDARD RATINGS

WV (Vdc)	Cap (μF)	Dimensions (mm)					Maximum ripple current (Arms)	WV (Vac)	Part Number	Previous Part Number (Just for your reference)			
		W	H	T	F	φd							
315	1.2	23.2	13.4	12.8	17.5	0.8	4.16	150	FTACB3B1V125JELHZO	TACB2F125J			
	1.5		14.8	14.1			4.65		FTACB3B1V155JELHZO	TACB2F155J			
	1.8		15.9	15.2			5.09		FTACB3B1V185JELHZO	TACB2F185J			
	2.2		17.3	16.5			5.63		FTACB3B1V225JELHZO	TACB2F225J			
	2.7		19.0	18.1			6.24		FTACB3B1V275JELHZO	TACB2F275J			
	3.3	28.2	18.6	17.7	22.5	1.0	5.47		FTACB3B1V335JFLEZO	TACB2F335J			
	3.9		20.0	19.0			5.95		FTACB3B1V395JFLEZO	TACB2F395J			
	4.7		21.8	20.7			6.53		FTACB3B1V475JFLEZO	TACB2F475J			
	5.6		23.6	22.5			7.13		FTACB3B1V565JFLEZO	TACB2F565J			
	6.8		25.8	24.6			7.86		FTACB3B1V685JFLEZO	TACB2F685J			
8.2	28.1	26.8	8.63	FTACB3B1V825JFLEZO	TACB2F825J								
400	0.1	16.2	9.2	8.8	10.0	0.8	2.40	175	FTACB401V104JDLCZO	TACB2G104J			
	0.12		9.7	9.3			2.62		FTACB401V124JDLCZO	TACB2G124J			
	0.15		10.5	10.1			2.93		FTACB401V154JDLCZO	TACB2G154J			
	0.18		11.2	10.7			3.21		FTACB401V184JDLCZO	TACB2G184J			
	0.22		12.1	11.6			3.55		FTACB401V224JDLCZO	TACB2G224J			
	0.27	18.2	13.1	12.5	12.5	0.8	3.94		FTACB401V274JDLCZO	TACB2G274J			
	0.33		13.2	12.6			3.71		FTACB401V334JHLGZO	TACB2G334J			
	0.39		14.1	13.5			4.04		FTACB401V394JHLGZO	TACB2G394J			
	0.47		15.2	14.5			4.43		FTACB401V474JHLGZO	TACB2G474J			
	0.56		14.1	13.5			3.54		FTACB401V564JELHZO	TACB2G564J			
	0.68	23.2	15.3	14.6	17.5	0.8	3.90		FTACB401V684JELHZO	TACB2G684J			
	0.82		16.6	15.8			4.29		FTACB401V824JELHZO	TACB2G824J			
	1.0		18.1	17.2			4.73		FTACB401V105JELHZO	TACB2G105J			
	1.2		19.6	18.6			5.19		FTACB401V125JELHZO	TACB2G125J			
	1.5		19.2	18.3			4.58		FTACB401V155JFLEZO	TACB2G155J			
	1.8	28.2	20.8	19.8	22.5	1.0	5.02		FTACB401V185JFLEZO	TACB2G185J			
	2.2		22.8	21.8			5.55		FTACB401V225JFLEZO	TACB2G225J			
	2.7		25.1	23.9			6.15		FTACB401V275JFLEZO	TACB2G275J			
	3.3		27.5	26.2			6.79		FTACB401V335JFLEZO	TACB2G335J			
	3.9		23.9	22.8			4.57		FTACB401V395JTLJZO	TACB2G395J			
4.7	43.2	25.9	24.7	37.5	1.0	5.02	FTACB401V475JTLJZO	TACB2G475J					
5.6		28.1	26.8			5.48	FTACB401V565JTLJZO	TACB2G565J					
630		0.056	16.2			8.5	8.2	10.0	0.8	1.96	200	FTACB631V563JDLCZO	TACB2J563J
		0.068				9.1	8.7			2.16		FTACB631V683JDLCZO	TACB2J683J
		0.082				9.6	9.2			2.38		FTACB631V823JDLCZO	TACB2J823J
	0.1	10.3		9.8	2.62	FTACB631V104JDLCZO	TACB2J104J						
	0.12	11.0		10.5	2.88	FTACB631V124JDLCZO	TACB2J124J						
	0.15	18.2	11.9	11.4	12.5	0.8	3.21	FTACB631V154JDLCZO	TACB2J154J				
	0.18		12.3	11.8			3.10	FTACB631V184JHLGZO	TACB2J184J				
	0.22		13.4	12.8			3.42	FTACB631V224JHLGZO	TACB2J224J				
	0.27		14.6	13.9			3.79	FTACB631V274JHLGZO	TACB2J274J				
	0.33		13.5	12.9			3.04	FTACB631V334JELHZO	TACB2J334J				
	0.39	23.2	14.5	13.8	17.5	0.8	3.30	FTACB631V394JELHZO	TACB2J394J				
	0.47		15.6	14.9			3.63	FTACB631V474JELHZO	TACB2J474J				
	0.56		16.8	16.0			3.96	FTACB631V564JELHZO	TACB2J564J				
	0.68		18.3	17.4			4.36	FTACB631V684JELHZO	TACB2J684J				
	0.82		19.9	18.9			4.79	FTACB631V824JELHZO	TACB2J824J				
	1.0	28.2	19.2	18.3	22.5	1.0	4.16	FTACB631V105JFLEZO	TACB2J105J				
	1.2		20.8	19.8			4.55	FTACB631V125JFLEZO	TACB2J125J				
	1.5		23.0	22.0			5.09	FTACB631V155JFLEZO	TACB2J155J				
	1.8		25.1	23.9			5.58	FTACB631V185JFLEZO	TACB2J185J				
	2.2		27.5	26.2			6.17	FTACB631V225JFLEZO	TACB2J225J				
2.7	43.2	23.8	22.7	37.5	1.0	4.17	FTACB631V275JTLJZO	TACB2J275J					
3.3		26.0	24.8			4.61	FTACB631V335JTLJZO	TACB2J335J					
3.9		28.0	26.7			5.01	FTACB631V395JTLJZO	TACB2J395J					

(1)Capacitance tolerance : Standard (J: ±5%) , Option (K:± 10%)

(2)The maximum ripple current : +85°Cmax., 100kHz, sine wave

(3)WV(Vac) : 50Hz or 60Hz, sine wave

◆STANDARD RATINGS

WV (Vdc)	Cap (μF)	Dimensions (mm)					Maximum ripple current (Arms)	WV (Vac)	Part Number	Previous Part Number (Just for your reference)
		W	H	T	F	φd				
800	0.033	16.2	9.0	8.6	10.0	0.8	1.81	250	FTACB801V333JDLCZ0	TACB2K333J
	0.039		9.5	9.1			1.97		FTACB801V393JDLCZ0	TACB2K393J
	0.047		10.1	9.7			2.16		FTACB801V473JDLCZ0	TACB2K473J
	0.056		10.8	10.3			2.36		FTACB801V563JDLCZ0	TACB2K563J
	0.068		11.5	11.0			2.60		FTACB801V683JDLCZ0	TACB2K683J
	0.082		12.5	11.9			2.85		FTACB801V823JDLCZ0	TACB2K823J
	0.1	18.2	12.3	11.8	12.5	0.8	2.67		FTACB801V104JHLGZ0	TACB2K104J
	0.12		13.3	12.7			2.92		FTACB801V124JHLGZ0	TACB2K124J
	0.15		14.6	13.9			3.26		FTACB801V154JHLGZ0	TACB2K154J
	0.18		13.4	12.8			2.59		FTACB801V184JELHZ0	TACB2K184J
	0.22	23.2	14.5	13.8	17.5	0.8	2.87		FTACB801V224JELHZ0	TACB2K224J
	0.27		15.8	15.1			3.17		FTACB801V274JELHZ0	TACB2K274J
	0.33		17.2	16.4			3.51		FTACB801V334JELHZ0	TACB2K334J
	0.39		18.5	17.6			3.82		FTACB801V394JELHZ0	TACB2K394J
	0.47		20.1	19.1			4.19		FTACB801V474JELHZ0	TACB2K474J
	0.56		28.2	19.2			18.3		22.5	1.0
	0.68	20.9		19.9	3.96	FTACB801V684JFLEZ0	TACB2K684J			
	0.82	22.8		21.8	4.35	FTACB801V824JFLEZ0	TACB2K824J			
	1.0	25.0		23.8	4.80	FTACB801V105JFLEZ0	TACB2K105J			
	1.2	27.2		25.9	5.26	FTACB801V125JFLEZ0	TACB2K125J			

- (1)Capacitance tolerance:Standard(J:±5%),Option(K:±10%)  
(2)The maximum ripple current : +85°C max., 100kHz, sine wave  
(3)WV(Vac) : 50Hz or 60Hz, sine wave

◆DIMENSIONS (mm)

