

The following series are discontinued. Please use the replacements in the table.

## ◆CHIP TYPE REPLACEMENTS

Discontinued series	Characteristics	Replacements	Page
MV	85°C standard	MVA	4-8
MVK	105°C standard	MVE	4-10
MKA			
MVZ	Low impedance	MZA	4-16
MZD	Low impedance, Long life	MZE	4-22

## ◆LEAD TYPE REPLACEMENTS

Discontinued series	Characteristics	Replacements	Page
SM	85°C standard	SMG	5-15
SME			
KM	105°C standard	KMG	5-18
KMC			
KME			
USM			
SHA	95°C L=7mm	LXY/LXZ	5-46/5-43
SM-BP	85°C bi-polar	*	—
KM-BP	105°C bi-polar	*	
SRC	85°C low profile	SRG	5-5
LXE	Low impedance	KY/LXV	5-38/5-48
LXJ			
SXE			
KMF(6.3 to 100V <sub>dc</sub> )			
LXF	Low impedance	LXY	5-46
KMY	Long life	KY	5-38
LXA	Long life	KY/LXY	5-38/5-46
KLJ	No sparks with DC overvoltage	KLJ	5-65
SMH	85°C large radial	SMG/PAG	5-15/5-63
KMH	105°C large radial	KMG/PAG	5-18/5-63
GXD	High heat resistance	GXE	5-83
GHA	150°C high heat resistance	*	—
KMF(160 to 450V <sub>ac</sub> )	High ripple current	KXG	5-57
KMX	Long life		
LLA	85°C low leakage current	*	—

## ◆SNAP-IN REPLACEMENTS

Discontinued series	Characteristics	Replacements	Page
SLM	85°C L=15mm	*	—

## ◆SCREW-MOUNT TERMINAL REPLACEMENTS

Discontinued series	Characteristics	Replacements	Page
LWY	105°C long life	LXA/LXR	7-28/7-32

\* Please contact us.

Already been discontinued products are not listed in this catalog.